

THE SELF SUPPORTING GOODS LIFT

ATTOLL



**Self Supporting Structure** - The SSGL600 with its innovative self supporting structure can be installed in virtually all types of location without the need for a pit or being anchored at the landings. Structural checks are not required.

**Modular** - The modular structure is optimised for pallets, roll cages, trolleys and for mezzanine floors with an adjustable stroke to 7M.

**Fast Installation** - A safe and effective solution to reach mezzanine floors. Installed quickly with no building works.

1 mm of 1

**One Touch** - One touch, press and release controls are included. Raises at the touch of a button in total safety.

**4.0 Smart Factory Ready** - Technology born for integration with automated smart industry 4.0 systems.

**Standardisation** - For reduced lead times and fast installations. Available with two platform sizes 1300mm x 1700mm and 1100mm x 1480mm

## TECHNICAL DATA

CAPACITY	MAX TRAVEL	STOPS	HEADROOM	DIMS.	O/A DIMS.
600Kg	7000mm	Max. 5	2300mm	1110 x 1440mm	1580 x 1780mm
				1300 x 1700mm	1780 x 2040mm

## STANDARD EQUIPMENT

- Goods only transport
- 2.2Kw, 3 phase powerpack
- 0.15M/S lift speed
- Bumper strips
- Self supporting structure in RAL7016 powder coated laser cut tubular steel sections
- Pressed steel cladding in powder coated RAL9006
- Manually operated fully interlocked swing door with single or double leaf with emergency release
- 100mm high load ramp to lowest floor

## OPTIONAL EQUIPMENT

- Goods and attendant on-board
- 0.30 M/S speed (goods only)
- Micro perforated steel cladding in RAL9006 powder coating
- Powered automated swing doors
- Powered automated roller shutters
- Overload control
- Cabinet to house powerpack and panel
- Smart industry 4.0 ready









Edmolift UK Ltd, Steeple Bumpstead, Cambridge, CB9 7BN

lifts@edmolift.co.uk T. 01440 730640

www.edmolift.co.uk www.loadingbaylift.com

